



1"

2.25 #

P-110

CS HYD

NOTE: THIS TECHNICAL INFORMATION IS FOR REFERENCE ONLY

PIPE BODY

OD (IN):	1.315
WALL THICKNESS (IN):	0.179
ID (IN):	0.957
TENSILE STRENGTH NEW (LBS):	70,000
TENSILE STRENGTH PREM (LBS):	56,000
BURST CAPACITY NEW (PSI):	26,200
BURST CAPACITY TEST (PSI):	23,000
COLLAPSE CAPACITY NEW (PSI):	25,870
COLLAPSE CAPACITY 80% (PSI):	20,696

ENGINEERING DATA

DRIFT DIAMETER (IN):	0.848
AVERAGE JOINT LENGTH (FT):	31
DISPLACEMENT, OPEN (GAL./FT.):	0.034
DISPLACEMENT, OPEN (BBL./100 FT.):	0.081
CAPACITY (GAL./FT.):	0.037
CAPACITY (BBL./100 FT.):	0.088

CONNECTION SPECS

OUTSIDE DIAMETER (IN):	1.6	MAKE UP MIN (FT-LBS):	400
INSIDE DIAMETER (IN):	0.864	MAKE UP MAX (FT-LBS):	500
TORSIONAL YIELD (FT-LBS):	1,357		