



2 3/8"

4.70 #

L-80

8RD

NOTE: THIS TECHNICAL INFORMATION IS FOR REFERENCE ONLY

PIPE BODY

	NOMINAL 100% RBW	87.5% RBW	PREMIUM 80% RBW
OD (IN):	2.375	2.328	2.299
WALL THICKNESS (IN):	0.190	0.166	0.152
ID (IN):	1.995	1.995	1.995
TENSILE STRENGTH (LBS):	104,338	90,304	82,019
TORSIONAL STRENGTH (FT-LBS):	5,081	4,383	3,974
BUST CAPACITY (PSI):	11,200	11,200	10,240
COLLAPSE CAPACITY (PSI):			

8RD CONNECTION

CONNECTION OD (IN):	3.063	CONNECTION TORSIONAL STRENGTH (FT-LBS):	N/A
CONNECTION ID (IN):	1.995	CONNECTION TENSILE STRENGTH (LBS):	104,300
THREADS PER INCH:	8	MAXIMUM MUT (FT-LBS):	2,200
MAKE-UP LOSS (IN):	N/A	OPTIMUM MUT (FT-LBS):	1,760
INTERNAL PRESSURE RATING (PSI):	11,200	MINIMUM MUT (FT-LBS):	1,320

TUBULAR ASSEMBLY

APPROXIMATE LENGTH (FT):	31	DRIFT SIZE (IN):	1.901
NOMINAL WEIGHT (LBS/FT):	4.70	COMPRESSION STRENGTH (LBS):	NOT REPORTED
MATERIAL GRADE:	L-80	MAX BENDING (DEGREES/100 FT):	NOT REPORTED