



**2 3/8"**

**5.95 #**

**P-110**

**PH6**

NOTE: THIS TECHNICAL INFORMATION IS FOR REFERENCE ONLY

## PIPE BODY

	NOMINAL 100% RBW	87.5% RBW	PREMIUM 80% RBW
OD (IN):	2.375	2.312	2.273
WALL THICKNESS (IN):	0.254	0.222	0.203
ID (IN):	1.867	1.867	1.867
TENSILE STRENGTH (LBS):	186,173	160,463	145,371
TORSIONAL STRENGTH (FT-LBS):	8,600	7,367	6,652
BUST CAPACITY (PSI):	20,587	20,587	18,823
COLLAPSE CAPACITY (PSI):			

## PH6 CONNECTION

CONNECTION OD (IN):	2.906	CONNECTION TORSIONAL STRENGTH (FT-LBS):	N/A
CONNECTION ID (IN):	1.805	CONNECTION TENSILE STRENGTH (LBS):	186,000
THREADS PER INCH:	6	MAXIMUM MUT (FT-LBS):	3,400
MAKE-UP LOSS (IN):	3.050	OPTIMUM MUT (FT-LBS):	3,100
INTERNAL PRESSURE RATING (PSI):	20,590	MINIMUM MUT (FT-LBS):	2,700

## TUBULAR ASSEMBLY

APPROXIMATE LENGTH (FT):	31	DRIFT SIZE (IN):	1.773
NOMINAL WEIGHT (LBS/FT):	5.95	COMPRESSION STRENGTH (LBS):	186,000
MATERIAL GRADE:	P-110	MAX BENDING (DEGREES/100 FT):	212