



2 7/8"

7.90 #

P-110

PH6

NOTE: THIS TECHNICAL INFORMATION IS FOR REFERENCE ONLY

PIPE BODY

	NOMINAL 100% RBW	87.5% RBW	PREMIUM 80% RBW
OD (IN):	2.875	2.806	2.765
WALL THICKNESS (IN):	0.276	0.242	0.221
ID (IN):	2.323	2.323	2.323
TENSILE STRENGTH (LBS):	247,889	214,024	194,099
TORSIONAL STRENGTH (FT-LBS):	14,160	12,167	11,005
BUST CAPACITY (PSI):	18,480	18,480	16,896
COLLAPSE CAPACITY (PSI):			

PH6 CONNECTION

CONNECTION OD (IN):	3.438	CONNECTION TORSIONAL STRENGTH (FT-LBS):	N/A
CONNECTION ID (IN):	2.265	CONNECTION TENSILE STRENGTH (LBS):	248,000
THREADS PER INCH:	6	MAXIMUM MUT (FT-LBS):	4,400
MAKE-UP LOSS (IN):	3.040	OPTIMUM MUT (FT-LBS):	4,000
INTERNAL PRESSURE RATING (PSI):	18,480	MINIMUM MUT (FT-LBS):	3,500

TUBULAR ASSEMBLY

APPROXIMATE LENGTH (FT):	31	DRIFT SIZE (IN):	2.229
NOMINAL WEIGHT (LBS/FT):	7.90	COMPRESSION STRENGTH (LBS):	248,000
MATERIAL GRADE:	P-110	MAX BENDING (DEGREES/100 FT):	175.0