



3 1/2"

9.30#

N-80

8RD

NOTE: THIS TECHNICAL INFORMATION IS FOR REFERENCE ONLY

PIPE BODY

	NOMINAL 100% RBW	87.5% RBW	PREMIUM 80% RBW
OD (IN):	3.500	3.437	3.398
WALL THICKNESS (IN):	0.254	0.222	0.203
ID (IN):	2.992	2.992	2.992
TENSILE STRENGTH (LBS):	207,215	179,540	163,178
TORSIONAL STRENGTH (FT-LBS):	15,089	13,039	11,833
BURST CAPACITY (PSI):	10,160	10,160	9,289
COLLAPSE CAPACITY (PSI):	10,535	8,595	7,396

EUE (8 RD) CONNECTION

CONNECTION OD (IN):	4.500	CONNECTION TORSIONAL STRENGTH (FT-LBS):	N/A
CONNECTION ID (IN):	2.992	CONNECTION TENSILE STRENGTH (LBS):	207,200
THREADS PER INCH:	8	MAXIMUM MUT (FT-LBS):	4,000
MAKE-UP LOSS (IN):	N/A	OPTIMUM MUT (FT-LBS):	3,200
INTERNAL PRESSURE RATING (PSI):	10,160	MINIMUM MUT (FT-LBS):	2,400

TUBULAR ASSEMBLY

APPROXIMATE LENGTH (FT):	31.0	DRIFT SIZE (IN):	2.867
NOMINAL WEIGHT (LBS/FT):	9.30	COMPRESSION FLUID CAPACITY(gal/ft):	0.3652
MATERIAL GRADE:	N-80	FLUID CAPACITY(bbls/ft):	0.0087