

**2 7/8"****6.50 #****L-80****8RD**

NOTE: THIS TECHNICAL INFORMATION IS FOR REFERENCE ONLY

PIPE BODY

	NOMINAL 100% RBW	87.5% RBW	PREMIUM 80% RBW
OD (IN):	2.875	2.821	2.788
WALL THICKNESS (IN):	0.217	0.190	0.174
ID (IN):	2.441	2.441	2.441
TENSILE STRENGTH (LBS):	144,962	125,547	114,076
TORSIONAL STRENGTH (FT-LBS):	8,621	7,445	6,754
BUST CAPACITY (PSI):	10,567	10,567	9,661
COLLAPSE CAPACITY (PSI):			

8RD CONNECTION

CONNECTION OD (IN):	3.668	CONNECTION TORSIONAL STRENGTH (FT-LBS):	N/A
CONNECTION ID (IN):	2.441	CONNECTION TENSILE STRENGTH (LBS):	145,000
THREADS PER INCH:	8	MAXIMUM MUT (FT-LBS):	2,810
MAKE-UP LOSS (IN):	N/A	OPTIMUM MUT (FT-LBS):	2,250
INTERNAL PRESSURE RATING (PSI):	10,570	MINIMUM MUT (FT-LBS):	1,690

TUBULAR ASSEMBLY

APPROXIMATE LENGTH (FT):	31	DRIFT SIZE (IN):	2.347
NOMINAL WEIGHT (LBS/FT):	6.50	COMPRESSION STRENGTH (LBS):	NOT REPORTED
MATERIAL GRADE:	L-80	MAX BENDING (DEGREES/100 FT):	NOT REPORTED